

DESCRIPTIVE

- Electronic governor
- Mechanically welded chassis with antivibration suspension
- Main line circuit breaker
- Radiator for core temperature of 48/50°C max with mechanical fan
- Protective grille for fan and rotating parts (CE option)
- 9 dB(A) silencer supplied separately
- Charger DC starting battery with electrolyte
- 24 V charge alternator and starter
- Delivered with oil and coolant -30°C
- Manual for use and installation

POWER DEFINITION

PRP : Prime Power is available for an unlimited number of annual operating hours in variable load applications, in accordance with ISO 8528-1. ESP : The standby power rating is applicable for supplying emergency power in variable load applications in accordance with ISO 8528-1. Overload is not allowed.

TERMS OF USE

According to the standard, the nominal power assigned by the genset is given for 25°C Air Inlet Temperature, of a barometric pressure of 100 kPa (100 m A.S.L), and 30 % relative humidity. For particular conditions in your installation, refer to the derating table.

ASSOCIATED UNCERTAINTY

For the generating sets used indoor, where the acoustic pressure levels depends on the installation conditions, it is not possible to specify the ambient noise level in the exploitation and maintenance instructions . You will also find in our exploitation and maintenance instructions a warning concerning the air noise dangers and the need to implement appropriated preventive measures.

V275C2

Engine ref.	TAD734GE
Alternator ref.	KH01421T
Performance class	G3

GENERAL CHARACTERISTICS

Frequency (Hz)	50 Hz
Voltage (V)	400/230
Standard Control Panel	APM403
Optional control panel	APM802
Optional Control Panel	M80
Optional control panel	Terminal block

POWER

Voltage	ESP		PRP		Standby Amps
	kWe	kVA	kWe	kVA	
415/240	220	275	200	250	383
400/230	220	275	200	250	397
380/220	211	264	192	240	401
200/115	220	275	200	250	794
240 TRI	220	275	200	250	662
230 TRI	220	275	200	250	690
220 TRI	220	275	200	250	722

DIMENSIONS COMPACT VERSION

Length (mm)	2900
Width (mm)	1300
Height (mm)	1590
Dry weight (kg)	2172
Tank capacity (L)	390

DIMENSIONS SOUNDPROOFED VERSION

Type soundproofing	M227
Length (mm)	4004
Width (mm)	1380
Height (mm)	2145
Dry weight (kg)	3102
Tank capacity (L)	390
Acoustic pressure level @1m in dB(A) 50Hz (75% PRP)	78
Sound power level guaranteed (Lwa) 50Hz (75% PRP)	97
Acoustic pressure level @7m in dB(A) 50Hz (75% PRP)	67

GENERAL ENGINE DATA

Engine brand	VOLVO
Engine ref.	TAD734GE
Air inlet system	Turbo
Cylinders configuration	L
Number of cylinders	6
Displacement (L)	7,15
Charge Air coolant	Air/Air
Bore (mm) x Stroke (mm)	108 x 130
Compression ratio	17.1 : 1
Speed (RPM)	1500
Pistons speed (m/s)	6,50
Maximum stand-by power at rated RPM (kW)	250
Frequency regulation, steady state (%) +/- 0.25%	
BMEP @ PRP 50 Hz (bar)	25,40
Governor type	Electronic

COOLING SYSTEM

Radiator & Engine capacity (L)	37
Fan power (kW)	3,80
Fan air flow w/o restriction (m3/s)	4,80
Available restriction on air flow (mm H2O)	20
Type of coolant	Glycol-Ethylene

EMISSIONS

Emission PM (g/kW.h)	0,05
Emission CO (g/kW.h)	0,35
Emission HC+NOx (g/kWh)	5,09
Emission HC (g/kW.h)	0,08

EXHAUST

Exhaust gas temperature @ ESP 50Hz (°C)	550
Exhaust gas flow @ ESP 50Hz (L/s)	557
Max. exhaust back pressure (mm H2O)	750

FUEL

Consumption @ 100% load ESP (L/h)	59,60
Consumption @ 100% PRP load (L/h)	53,40
Consumption @ 75% PRP load (L/h)	42,60
Consumption @ 50% PRP load (L/h)	30,50
Maximum fuel pump flow (L/h)	300

OIL

Oil system capacity including filters (L)	29
Min. oil pressure (bar)	1
Max. oil pressure (bar)	4,50
Oil consumption 100% ESP 50Hz (L/h)	0,01
Oil sump capacity (L)	24

HEAT BALANCE

Heat rejection to exhaust (kW)	
Radiated heat to ambient (kW)	7
Heat rejection to coolant HT (kW)	129

AIR INTAKE

Max. intake restriction (mm H2O)	300
Intake air flow (L/s)	272

GENERAL DATA

Alternator ref.	KH01421T
Number of Phase	Three phase
Power factor (Cos Phi)	0,80
Altitude (m)	0 à 1000
Overspeed (rpm)	2250
Number of pole	4
Capacity for maintaining short circuit at 3 In for 10 s	No
Insulation class	H
T° class (H/125°), continuous 40°C	H / 125°K
T° class (H/163°C), standby 27°C	H / 163°K
Total Harmonic Distortion in no-load DHT (%)	<2.5
AVR Regulation	Yes
Total Harmonic Distortion, on linear load DHT (%)	<2.5
Wave form : NEMA=TIF	<50
Wave form : CEI=FHT	<2
Number of bearing	Single Bearing
Coupling	Direct
Voltage regulation at established rating (+/- %)	0,50
Recovery time (Delta U = 20% transient) (ms)	500
Indication of protection	IP 23
Technology	Brushless

OTHER DATA

Continuous Nominal Rating 40°C (kVA)	250
Standby Rating 27°C (kVA)	275
Efficiencies 100% of load (%)	92,70
Air flow (m3/s)	0,48
Short circuit ratio (Kcc)	0,3640
Direct axis synchro reactance unsaturated (Xd) (%)	369
Quadra axis synchro reactance unsaturated (Xq) (%)	188
Open circuit time constant (T'do) (ms)	2452
Direct axis transient reactance saturated (X'd) (%)	15
Short circuit transient time constant (T'd) (ms)	100
Direct axis subtransient reactance saturated (X''d) (%)	12
Subtransient time constant (T''d) (ms)	10
Quadra axis subtransient reactance saturated (X''q) (%)	15,90
Subtransient time constant (T''q) (ms)	10
Zero sequence reactance unsaturated (Xo) (%)	0,60
Negative sequence reactance saturated (X2) (%)	13,98
Armature time constant (Ta) (ms)	15
No load excitation current (io) (A)	0,78
Full load excitation current (ic) (A)	3,32
Full load excitation voltage (uc) (V)	44,60
Engine start (Delta U = 20% perm. or 30% trans.) (kVA)	560,65
Transient dip (4/4 load) - PF : 0,8 AR (%)	13
No load losses (W)	3660,49
Heat rejection (W)	15662,4
Unbalanced load acceptance ratio (%)	2
	100

DIMENSIONS

Dimensions soundproofed version

Type soundproofing	M227
Length (mm)	4004
Width (mm)	1380
Height (mm)	2145
Dry weight (kg)	3102
Tank capacity (L)	390
Acoustic pressure level @1m in dB(A) 50Hz (75% PRP)	78
Sound power level guaranteed (Lwa) 50Hz (75% PRP)	97
Acoustic pressure level @7m in dB(A) 50Hz (75% PRP)	67

Dimensions DW soundproofed version


Type soundproofing	M227 DW
Length (mm)	4056
Width (mm)	1380
Height (mm)	2340

Dimensions DW compact version

Type soundproofing	
Length (mm)	4056
Width (mm)	1360
Height (mm)	1801
Dry weight (kg)	2902
Tank capacity (L)	950
Acoustic pressure level @1m in dB(A) 50Hz (75% PRP)	
Sound power level guaranteed (Lwa) 50Hz (75% PRP)	
Acoustic pressure level @7m in dB(A) 50Hz (75% PRP)	

Dry weight (kg)	3815
Tank capacity (L)	950
Acoustic pressure level @1m in dB(A) 50Hz (75% PRP)	77
Sound power level guaranteed (Lwa) 50Hz (75% PRP)	97
Acoustic pressure level @7m in dB(A) 50Hz (75% PRP)	67

APM403, basic generating set and power plant control



The APM403 is a versatile control unit which allows operation in manual or automatic mode
 Measurements : voltage and current
 kW/kWh/kVA power meters
 Standard specifications: Voltmeter, Frequency meter.
 Optional : Battery ammeter.
 J1939 CAN ECU engine control
 Alarms and faults: Oil pressure, Coolant temperature, Overspeed, Start-up failure, alternator min/max, Emergency stop button.
 Engine parameters: Fuel level, hour counter, battery voltage.
 Optional (standard at 24V): Oil pressure, water temperature.
 Event log/ Management of the last 300 genset events.
 Mains and genset protection
 Clock management
 USB connections, USB Host and PC,
 Communications : RS485 INTERFACE
 ModBUS protocol /SNMP
 Optional : Ethernet, GPRS, remote control, 3G, 4G,
 Websupervisor, SMS, E-mails

APM802 dedicated to power plant management



The new APM802 command/control system is specifically designed for operating and monitoring power plants for markets including hospitals, data centres, banks, the oil and gas sector, industries, IPP, rental and mining.
 This unit is available as standard on all generating sets from 275 Kva designed for coupling. It is optional on the rest of our range.

The Human Machine Interface, designed in collaboration with a company specialising in interface design, facilitates operations with a large 100% touch screen. The pre-configured system for power plant applications features a brand new customisation function which complies with the international standard IEC 61131-3. New communication functions (PLC and regulation), improve the high level of equipment availability in the installation.

Advantages:
 Dedicated to power plant management.
 Specially researched ergonomics.
 High level of equipment availability.
 Modularity and long service life guaranteed.
 Making it easy to extend the installation

For more information, please refer to the sales documentation.

M80, transfer of information



The M80 is a dual-function control unit. It can be used as a basic terminal block for connecting a control box and as an instrument panel with a direct read facility, with displays giving a global view of your generating set's basic parameters.

Offers the following functions:

Engine parameters: tachometer, working hours counter, coolant temperature indicator, oil pressure indicator, emergency stop button, customer connection terminal block, CE.

Basic terminal block



The control unit can be used as a basic terminal block for connecting a control box.

Offers the following functions:

emergency stop button, customer connection terminal block, CE.